



PRODUCT SPECIFICATION

MODEL: WTP101A0

< ◆ > PRELIMINARY SPECIFICATION

< ◇ > APPROVAL SPECIFICATION

CUSTOMER
APPROVED BY
DATE:

DESIGNED	CHECKED	APPROVED

PREPARED BY:

W DISPLY TECHNOLOGIES CO., LTD.

1002-A, B&Q CENTER, CENTRAL WEALTH DISTRICT, NANCHENG, DONGGUAN, GUANGDONG, CHINA

TEL : +86-769-22823699

FAX : +86-769-22823665

RD@w-display.com



REVISION STATUS

Version	Revise Date	Page	Content	Modified by
V1.0	2010.01.06	-	First issue	Kandy

www.w-display.com Confidential

**Technology:**

- PC-TP (Projective Capacitive Touch Panel)
 MR-TP (Multiple-Touch Resistive Touch Panel)
 DR-TP (Dual-Touch 4-wires Resistive Touch Panel)

Applications:

- Mobile phone Media Player GPS MID Gaming Industrial NB
 AIO Others

Features:

- (A) Two touches independence.
 (B) HID compatible for Win 7.
 (C) A real "soft" touch without any writing force on touch panel

Specification:

Item	Description	Unit
Size	10.1	inch
View Area	226.2 ±0.1 * 127.1 ±0.1	mm
Outline Area	231.10±0.3 * 134.8±0.3	mm
Transmittance	> 85% (Note 1)	-
TP Resolution	1024 x 600	Dot

Note1: Transmittance includes ITO touch sensor, cover-lens and lamination.

TP Measurement Result: (Note 2)

Item	Description	Unit
Line Accuracy	≤ 2	mm
Static Resolution	≤ 2 coordinate deviation @ 10 times repeated touch	-
Data update rate	20	ms
Proximity	0	mm
Jitter	≤ 1 coordinate deviation @ 2Kg weight	-
SNR	5~10	-

Note2: Those test items are conducted by the tester of NASTECH-MT00XC developed at NAS proprietary.